

APARATAJ ELECTRIC DE JOASA TENSIUNE
DIVERSE APARATE ELECTRICE
LOW VOLTAGE ELECTRICAL APPARATUS
VARIED ELECTRICAL APPARATUS

| Produs Product | Denumire / Caracteristici Denomination/ Characteristics | Tip / Cod Type/ Code |
|-------------------|--|-------------------------|
|-------------------|--|-------------------------|



Priza modulara cu 1- 6 prize cu
contact de protectie pe tencuiala

PM – 1-6 CP-PT
N – 02548/1-6

- Priza este destinata conectarii in instalatiile electrice de joasa tensiune a aparatelor electrocasnice.
- **Caracteristici generale :**
- Temperatura in timpul utilizarii: -33⁰....+55⁰C.
- Umiditatea relativa a aerului: max.80% la temperatura de 20⁰C si max. 50% la temperatura de 40⁰C.
- **Caracteristici tehnice :**
- Tensiunea maxima de utilizare : 250V~.
- Curent nominal : 16A.
- Standard aferent : SR CEI 60884-1/2003.

EXEMPLU DE COMAND~ :

Priza modulara cu 1-6 prize cu contact
de protectie pe tencuiala

PM – 1-6CP-PT

N – 02548/1-6

16 A

Denumire

Simbol

Cod

Curent
maxim

S.C. RELEE S.A.

551061Media] – ROM^NIA
Str. Gloria nr.5

Tel. 0269 / 845901, 2, 3

Fax. 0269 / 831231

e-mail:office@relee.ro

N – 443150