



Caracteristici

	CM-660	CM-860	CM-960	CM-1360	CM-1560
Masurare valoare reala True RMS	AC	AC	AC+DC	AC	AC+DC
Peak RMS			✓		✓
Crest					✓
Lanterna				✓	✓
Lumina fundal		✓	✓	✓	✓
Relative Offset Mode (Δ)		✓	✓	✓	✓
AmpTip™	✓	✓	✓	✓	✓
VFD ACV, Frecventa Hz	✓	✓	✓	✓	✓
Detectare tensiune fara contact	✓	✓	✓	✓	✓
Maximum / Minimum / Medie	✓	✓	✓	✓	✓
Frecventa	✓	✓	✓	✓	✓
Continuitate / Test dioda	✓	✓	✓	✓	✓
Memorare valoare masurata	✓	✓	✓	✓	✓
Oprire automata	✓	✓	✓	✓	✓

INTERVALE

Capacitate		2500 μ F	2500 μ F	2500 μ F	2500 μ F
Masurare curent DC			600		1000
Masurare curent AC	600	600	600	1000	1000
Masurare tensiune DC	600	600	600	1000	1000
Masurare tensiune AC	600	600	600	1000	1000
Rezistenta	60 k Ω	60 k Ω	60 k Ω	60 k Ω	60 k Ω
Display	6000	6000	6000	6000	6000
Categoria de masurare	CAT IV 300V CAT III 600V	CAT IV 300V CAT III 600V	CAT IV 300V CAT III 600V	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V