

12A	APLICATII	CARACTERISTICI
DUZA PT. ASPERSOR Pro-Spray	rezidential	pulverizare fina, unghi ajustabil 0-360°

12A

Raza : 3.6m

Unghi	Presiune	Raza m	Debit		Precipit. mm/h	
	Bar		m ³ /h	l/min	□	Δ
45°	1	2.7	0.05	0.83	53	61
	1.5	3.2	0.06	1	47	55
	2	3.7	0.07	1.17	42	48
	2.1	4	0.07	1.17	36	42
	2.5	4.2	0.08	1.33	36	42
90°	1	2.7	0.1	1.67	53	61
	1.5	3.2	0.12	2	47	55
	2	3.7	0.14	2.33	42	48
	2.1	4	0.15	2.5	36	42
	2.5	4.2	0.16	2.67	36	42
120°	1	2.7	0.13	2.17	53	61
	1.5	3.2	0.16	2.67	47	55
	2	3.7	0.19	3.17	42	48
	2.1	4	0.19	3.17	36	42
	2.5	4.2	0.21	3.5	36	42
180°	1	2.7	0.19	3.17	53	61
	1.5	3.2	0.24	4	47	55
	2	3.7	0.28	4.67	42	48
	2.1	4	0.29	4.83	36	42
	2.5	4.2	0.32	5.33	36	42
240°	1	2.7	0.26	4.33	53	61
	1.5	3.2	0.32	5.33	47	55
	2	3.7	0.38	6.33	42	48
	2.1	4	0.39	6.5	36	42
	2.5	4.2	0.43	7.17	36	42
270°	1	2.7	0.29	4.83	53	61
	1.5	3.2	0.36	6	47	55
	2	3.7	0.43	7.17	42	48
	2.1	4	0.44	7.33	36	42
	2.5	4.2	0.48	8	36	42
360°	1	2.7	0.39	6.5	53	61
	1.5	3.2	0.49	8.17	47	55
	2	3.7	0.57	9.5	42	48
	2.1	4	0.58	9.67	36	42
	2.5	4.2	0.64	10.67	36	42