

15A	APLICATII	CARACTERISTICI
DUZA PT. ASPERSOR Pro-Spray	rezidential	pulverizare fina, unghi ajustabil 0-360°

15A

Raza : 4.5m

Unghi	Presiune	Raza	Debit		Precipit. mm/h	
	Bar		m	m ³ /h	l/min	□
45°	1	3.4	0.07	1.17	50	57
	1.5	3.9	0.09	1.5	47	54
	2	4.6	0.1	1.67	40	46
	2.1	4.9	0.11	1.83	36	41
	2.5	5.2	0.12	2	35	40
90°	1	3.4	0.14	2.33	50	57
	1.5	3.9	0.18	3	47	54
	2	4.6	0.21	3.5	40	46
	2.1	4.9	0.22	3.67	36	41
	2.5	5.2	0.24	4	35	40
120°	1	3.4	0.19	3.17	50	57
	1.5	3.9	0.24	4	47	54
	2	4.6	0.28	4.67	40	46
	2.1	4.9	0.29	4.83	36	41
	2.5	5.2	0.32	5.33	35	40
180°	1	3.4	0.29	4.83	50	57
	1.5	3.9	0.36	6	47	54
	2	4.6	0.42	7	40	46
	2.1	4.9	0.43	7.17	36	41
	2.5	5.2	0.47	7.83	35	40
240°	1	3.4	0.38	6.33	50	57
	1.5	3.9	0.48	8	47	54
	2	4.6	0.56	9.33	40	46
	2.1	4.9	0.57	9.5	36	41
	2.5	5.2	0.63	10.5	35	40
270°	1	3.4	0.43	7.17	50	57
	1.5	3.9	0.54	9	47	54
	2	4.6	0.63	10.5	40	46
	2.1	4.9	0.65	10.83	36	41
	2.5	5.2	0.71	11.83	35	40
360°	1	3.4	0.57	9.5	50	57
	1.5	3.9	0.72	12	47	54
	2	4.6	0.84	14	40	46
	2.1	4.9	0.86	14.33	36	41
	2.5	5.2	0.95	15.83	35	40