

17A	APLICATII	CARACTERISTICI
DUZA PT. ASPERSOR Pro-Spray	rezidential	pulverizare fina, unghi ajustabil 0-360°

17A

Raza : 5m

Unghi	Presiune	Raza m	Debit		Precipit. mm/h	
	Bar		m ³ /h	l/min	□	Δ
45°	1	4.7	0.09	1.5	33	39
	1.5	4.9	0.12	2	38	44
	2	5.2	0.14	2.33	40	46
	2.1	5.5	0.14	2.33	37	42
	2.5	5.7	0.15	2.5	38	43
90°	1	4.7	0.18	3	33	39
	1.5	4.9	0.23	3.83	38	44
	2	5.2	0.27	4.5	40	46
	2.1	5.5	0.28	4.67	37	42
	2.5	5.7	0.31	5.17	38	43
120°	1	4.7	0.25	4.17	33	39
	1.5	4.9	0.31	5.17	38	44
	2	5.2	0.36	6	40	46
	2.1	5.5	0.37	6.17	37	42
	2.5	5.7	0.41	6.83	38	43
180°	1	4.7	0.37	6.17	33	39
	1.5	4.9	0.46	7.67	38	44
	2	5.2	0.54	9	40	46
	2.1	5.5	0.56	9.33	37	42
	2.5	5.7	0.61	10.17	38	43
240°	1	4.7	0.49	8.17	33	39
	1.5	4.9	0.62	10.33	38	44
	2	5.2	0.72	12	40	46
	2.1	5.5	0.74	12.33	37	42
	2.5	5.7	0.82	13.67	38	43
270°	1	4.7	0.55	9.17	33	39
	1.5	4.9	0.69	11.5	38	44
	2	5.2	0.81	13.5	40	46
	2.1	5.5	0.83	13.83	37	42
	2.5	5.7	0.92	15.33	38	43
360°	1	4.7	0.74	12.33	33	39
	1.5	4.9	0.92	15.33	38	44
	2	5.2	1.08	18	40	46
	2.1	5.5	1.11	18.5	37	42
	2.5	5.7	1.22	20.33	38	43