


Conectica izolata tip auto



■ Fisa plata izolata, mama 0.5 - 6 mm²

■ Pentru conductoare multifilare fine si extrafine

Caracteristici


- Izolatie sintetica: poliamida
- Codificare pe culori dupa normele in vigoare

Material

- CuZn (alama)

Suprafata

- Stanata



Sectiune mm ²	Cod	Culoare	Cote conf. DIN	Gros. mat	Latime	Dimensiune mm			Material izolant	Greutate/ 100 buc ~ kg	buc/cutie
						l1	l2	s			
0.5-1	8201	■		0.5	2.8	17.5	8.0	0.30	PVC	0.035	100
	8201A	■		0.8	2.8	17.5	8.0	0.30	PVC	0.045	100
	8202	■		0.5	4.8	18.0	6.0	0.35	PVC	0.065	100
	8203	■	4.8 – 1	0.8	4.8	18.0	6.0	0.35	PVC	0.065	100
	720	■	6.3 – 1	0.8	6.3	22.0	7.5	0.45	PVC	0.090	100
	7208	■		0.8	7.7	25.0	9.5	0.40	PVC	0.110	100
1.5-2.5	8301	■		0.5	2.8	18.0	8.0	0.35	PA	0.050	100
	8301A	■		0.8	2.8	18.0	8.0	0.35	PA	0.060	100
	8302	■		0.5	4.8	18.0	6.0	0.35	PVC	0.070	100
	8303	■	4.8 – 1	0.8	4.8	18.0	6.0	0.35	PVC	0.070	100
	730	■	6.3 – 2.5	0.8	6.3	21.0	7.4	0.45	PVC	0.090	100
	7308	■		0.8	7.7	25.0	9.5	0.45	PVC	0.115	100
4-6	8503	■		0.8	4.8	23.0	7.5	0.45	PA	0.138	100
	750	■	6.3 – 6	0.8	6.3	21.0	7.5	0.45	PVC	0.100	100
	7509	■		1.2	9.5	26.5	12.0	0.45	PVC	0.150	100