













CERTIFICATION AND CLASSIFICATION		Premium
Type of flooring	EN 651	Resilient residential vinyl floor covering
CE certification		 yes
Classification	ISO 10874	 Residential: 23 Commercial: 31
TECHNICAL CHARACTERISTICS		STANDARD
Extreme protection PUR reinforcement		Premium yes
Total thickness	ISO 24346	 3,20 mm
Wear layer thickness	ISO 24340	 0,30 mm
Total weight	ISO 23997	 2,30 kg/m <sup>2</sup>
Form of delivery - Rolls	ISO 24341	 28 lm (15 - 28 lm) x 2,5/3/3,5 m 25 lm (15 - 25 lm) x 4 m
Wear layer binder content		Type 1
TECHNICAL PERFORMANCES		STANDARD
Dimensional stability	ISO 23999	 ≤ 0,1%
Reaction to fire	ISO 13501-1	 Cfl - s1; report No: 212/BP/09
Residual indentation	ISO 24343-1	 ≤ 0,35 mm
Impact sound reduction	ISO 717/2	 16 dB
Underfloor heating		 Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance		Does not contribute to infection spreading
Castor chair test	ISO 4918	 Excellent
Light fastness	ISO 105 B02 - Method 3	7/8
Thermal resistance	DIN 52612	0,03 m <sup>2</sup> K/W



	 EN 14041 : 2004  DS  EN 13893  EN 1815  EN 12524	Manufactured by: Tarkett D.O.O. Industrijska Zona 14 21400 Bačka Palanka SERBIA
---	--	---