

PGP	APLICATII	RAZA	DEBIT
ASPERSOR ESCAMOTABIL ROTATIV	residential / comercial	4.9 ÷ 14.0 m	0.07 ÷ 3.23 m ³ /h

CARACTERISTICI

Model ridicare 10cm

Unghi ajustabil : de la 50 la 360°

Duze incluse : un set de 12 duze standard

Capac de cauciuc

CARACTERISTICI FUNCTIONARE

Raza : 8.2 ÷ 15.8m

Debit : 0.10 ÷ 3.22 m³/h; 1.7 ÷ 53.7 l/min

Presiunea recomandata : 1.7 ÷ 4.5bar; 170 ÷ 450kPa

Presiunea de functionare : 1.4 ÷ 7bar; 140 ÷ 700kPa

Rata de precipitatie : aprox. 10mm/h

Traectoria jetului : 25°

DIMENSIUNI

Inaltimea totala : 19cm

Diametru expus : 4.5cm

Sistem de prindere : ¾" Fi

DUZE ROSII STANDARD

Duza	Presiune Bar	Raza m	Debit		Precipit. mm/h	
			m ³ /h	l/min	□	Δ
1	1.7	8.2	0.1	1.7	3	3
	2	8.5	0.11	1.8	3	3
	2.5	8.5	0.13	2.2	4	4
	3	8.8	0.15	2.5	4	4
	3.5	8.8	0.16	2.7	4	5
	4	9.1	0.18	3	4	5
2	4.5	9.1	0.19	3.2	5	5
	1.7	8.5	0.14	2.3	4	5
	2	8.8	0.16	2.7	4	5
	2.5	8.8	0.17	2.8	4	5
	3	9.1	0.19	3.2	5	5
	3.5	9.1	0.21	3.5	5	6
3	4	9.4	0.22	3.7	5	6
	4.5	9.4	0.23	3.8	5	6
	1.7	8.8	0.18	3	5	5
	2	9.1	0.2	3.3	5	5
	2.5	9.1	0.22	3.7	5	6
	3	9.4	0.25	4.2	6	6
4	3.5	9.4	0.27	4.5	6	7
	4	9.8	0.29	4.8	6	7
	4.5	9.8	0.31	5.2	6	7
	1.7	9.4	0.24	4	5	6
	2	9.8	0.27	4.5	6	6
	2.5	9.8	0.3	5	6	7
5	3	10.1	0.34	5.7	7	8
	3.5	10.1	0.37	6.2	7	8
	4	10.4	0.4	6.7	7	9
	4.5	10.4	0.43	7.2	8	9
	1.7	10.1	0.33	5.5	7	8
	2	10.4	0.36	6	7	8
6	2.5	10.4	0.39	6.5	7	8
	3	11	0.43	7.2	7	8
	3.5	11.6	0.46	7.7	7	8
	4	11.6	0.49	8.2	7	8
	4.5	11.6	0.51	8.5	8	9
	1.7	10.1	0.42	7	8	10
7	2	10.4	0.45	7.5	8	10
	2.5	10.7	0.51	8.5	9	10
	3	11	0.57	9.5	9	11
	3.5	11.6	0.61	10.2	9	11
	4	11.6	0.66	11	10	11
	4.5	11.9	0.7	11.7	10	11

DUZE ROSII STANDARD

Duza	Presiune Bar	Raza m	Debit		Precipit. mm/h	
			m ³ /h	l/min	□	Δ
8	1.7	10.1	0.54	9	11	12
	2	10.4	0.58	9.7	11	12
	2.5	11	0.65	10.8	11	12
	3	11.6	0.72	12	11	12
	3.5	12.2	0.78	13	10	12
	4	12.2	0.83	13.8	11	13
9	4.5	12.2	0.88	14.7	12	14
	1.7	11	0.66	11	11	13
	2	11.3	0.71	11.8	11	13
	2.5	11.6	0.79	13.2	12	14
	3	11.9	0.87	14.5	12	14
	3.5	12.5	0.94	15.7	12	14
10	4	12.5	1	16.7	13	15
	4.5	12.8	1.05	17.5	13	15
	1.7	11.3	0.73	12.2	11	13
	2	11.6	0.8	13.3	12	14
	2.5	11.6	0.92	15.3	14	16
	3	12.5	1.05	17.5	13	16
11	3.5	13.4	1.15	19.2	13	15
	4	13.4	1.25	20.8	14	16
	4.5	13.7	1.35	22.5	14	17
	1.7	12.2	1.14	19	15	18
	2	12.8	1.29	21.5	16	18
	2.5	13.4	1.44	24	16	18
12	3	14	1.56	26	16	18
	3.5	14.3	1.68	28	16	19
	4	14.3	1.79	29.8	17	20
	4.5	14.6	1.9	31.7	18	21
	1.7	12.8	1.55	25.8	19	22
	2	13.7	1.73	28.8	18	21
13	2.5	14	1.9	31.7	19	22
	3	14.6	2.05	34.2	19	22
	3.5	14.9	2.18	36.3	20	23
	4	15.2	2.3	38.3	20	23
	4.5	15.5	2.42	40.3	20	23
	1.7	12.8	2.03	33.8	25	29
14	2	13.4	2.26	37.7	25	29
	2.5	14.3	2.51	41.8	24	28
	3	14.6	2.7	45	25	29
	3.5	14.9	2.88	48	26	30
	4	15.2	3.06	51	26	30
	4.5	15.8	3.22	53.7	26	30