



ISOSTUD 400

1213-CPD-4454

EN 13967

Membrana de protectie

Type V according EN 13967

MEMBRANE

Raw material /Material			HDPE
visible defects /defecte vizibile	EN 1850-2		free
length/lungime	EN 1848-2	m	20
width /latime	EN 1848-2	m	2,4/4,8
mass/masa	EN 1849-2	g/m ²	400
watertightness /impermeabilizare la apa	EN 1928		Pass (60kpa/24h)
resistance to tearing /rezistenta la sfasiere	EN 12310-1	N	npd
joint strenght /rezistenta la imbinari	EN 12317-2		npd
resistance to impact/rezistenta la impact	EN 12691	mm	<450
tensile properties m/c /rezistenta la tractiune	EN 12311-2	N/50mm	>200/200
elongation /alungirea la rupere	EN 12311-2	%	>40
resistance to deformation under load rezistenta la deformare sub incarcatura statica.	EN 13967	mm	<3

OTHER INFO

resistance against oxidation/rezistenta la oxidare	EN 1296		Pass
compression resistance/rezistenta la compresiune	EN ISO 25619-2	kN/m ²	>100
fire properties/clasa de combustibilitate	EN 13501-1	CLASS	F

The information given in this data sheet is to the best of our knowledge true and correct, however new research results and practical experience can make revisions necessary. No guarantee or liability can be drawn from the information mentioned herein.



Tegola Romania SRL
Sos.Pogonele, nr.18, Buzau -
Tel. +40 238 718181 - Fax +40 238719191
e - mail : office@tegora.ro

rev.1 14/11/08